PATENT Attorney Docket No. 915-001.053

10/529705 JC17 Rec'd PCT/PTO 29 MAR 2005

IN THE CLAIMS:

On page 16 at line 1, please delete "Claims" and insert -- What is Claimed is:-- therefor.

Please amend the claims as follows:

- 1. (currently amended) A method for indicating one or more terminal capability requirements for point-to-multipoint MBMS (Multimedia Broadcast/Multicast Service) service reception in a wireless system, characterized in that said method comprises the step of
 - -transmitting a broadcast or multicast message indicating said terminal capability requirements over the air interface to at least one terminal within the service range in order to allow the terminal to determine whether it is capable of receiving the service or not (822), said requirements being indicated in relation to at least one of the following: time slot configuration, modulation type, bit rate, <u>and</u> capability class.
- 2. (original) The method of claim 1, characterized in that a decision of whether to receive the service or not is made in the terminal on the basis of said indication.
- 3. (currently amended) The method of claim [[1-2]] 1, characterized in that it further comprises a step wherein said requirements for receiving the service are defined (820).
- 4. (currently amended) The method of claim [[1-2]] 1, characterized in that it further comprises a step wherein the service-related data is transmitted in conformity with indicated requirements (824).
- 5. (currently amended) The method of claim [[1-2]] 1, characterized in that said requirements are indicated in said message implicitly with an identifier associated to a certain set of requirements.
- 6. (currently amended) The method of claim [[1-2]] 1, characterized in that said requirements are indicated in said message explicitly with parameters.

- 7. (currently amended) The method of claim [[1-6]] 1, characterized in that said system is substantially GSM (Global System for Mobile communication)/GPRS (General Packet Radio Service) or UMTS (Universal Mobile Telecommunications System) system.
- 8. (currently amended) The method of claim [[1-7]] 1, characterized in that said message is transmitted to the terminals over radio access network.
- 9. (original) The method of claim 8, characterized in that said radio access network is GERAN (GSM/EDGE Radio Access Network) or UTRAN (UMTS Terrestrial Radio Access Network).
- 10. (currently amended) The method of claim [[1-8]] 1, characterized in that said message is originated by a network element.
- 11. (currently amended) The method of claim [[1-10]] 1, characterized in that said message is sent by the CBC (Cell Broadcast Centre) or RNC/BSC (Radio Network Controller/BaseStation Controller).
- 12. (currently amended) The method of claim [[1-8]] 1, characterized in that said message is substantially a schedule message.
- 13. (original) The method of claim 12, characterized in that said schedule message is CBS (Cell Broadcast Service) service specific.
- 14. (currently amended) The method of claim [[1-6]] 1, characterized in that said message is a discrete indication message.
- 15. (original) A method for indicating requirements for point-to-multipoint MBMS (Multimedia Broadcast/Multicast Service) service reception in a wireless system to be performed by a terminal operable in said system, characterized in that said method comprises the step of

-informing the terminal's capabilities in relation to at least one of the following: time slot configuration, modulation type, bit rate, and capability class, to said system in order to enable the system to deduce on the basis of the informed data whether the terminal is capable of receiving the service or not (804).

- 16. (original) The method of claim 15, **characterized** in that it further comprises a step (806) wherein the system either accepts or rejects the terminal's join request based on said deduction.
- 17. (original) The method of claim 15, **characterized** in that said system is substantially GSM (Global System for Mobile communication)/GPRS (General Packet Radio Service) or UMTS (Universal Mobile Telecommunications System) system.
- 18. (original) The method of claim 15, characterized in that said informing is performed over a radio access network that is substantially GERAN (GSM/EDGE Radio Access Network) or UTRAN (UMTS Terrestrial Radio Access Network).
- 19. (currently amended) The method of claim 15, characterized in that said informed data indicates at least one of the following features supported by said terminal: time slot configuration, modulation type, bit rate, and capability class.
- 20. (currently amended) The method of claim [[15-16]] 15, characterized in that it further comprises a step wherein the service-related data is transmitted in conformity with indicated requirements (810).
- 21. (currently amended) The method of claim [[16-20]] 16, characterized in that said point-to-multipoint service is substantially a multicast service.
- 22. (currently amended) The method of claim [[16-20]] 16, characterized in that the air interface in said system is substantially in accordance with DVB (Digital Video Broadcasting) or WLAN (Wireless Local Area Network) specifications.
- 23. (original) A terminal (900) operable (904, 906, 914, 915) in a wireless system, comprising processing means (908) and memory means (910) for processing and storing instructions and data, **characterized** in that said terminal is arranged to receive a message indicating requirements for point-to-multipoint MBMS (Multimedia Broadcast/Multicast Service) service reception and further arranged to determine on the basis of said requirements whether it is capable of receiving the service or not, said requirements indicated in relation to

at least one of the following: time slot configuration, modulation type, bit rate, and capability class.

- 24. (original) The terminal of claim 23, characterized in that it is arranged to specify said requirements indicated in said message by associating at least one identifier included in said message to a certain set of requirements.
- 25. (original) The terminal of claim 23, characterized in that it is arranged to extract said requirements directly from said message wherein said requirements are described explicitly.
- 26. (original) The terminal of claim 23, characterized in that said message to be received is a point-to-multipoint message.
- 27. (original) The terminal of claim 23, characterized in that it is substantially a GSM (Global System for Mobile communication) or UMTS (Universal Mobile Telecommunications System) terminal.
- 28. (original) The terminal of claim 23, characterized in that it is arranged to extract said indications of service requirements from a schedule message.
- 29. (original) The terminal of claim 23, characterized in that it is arranged to receive said message from the system over the air interface congruent with DVB (Digital Video Broadcasting) or WLAN (Wireless Local Area Network) specifications.
- 30. (original) A terminal (900) operable (904, 906, 914, 915) in a wireless system, comprising processing means (908) and memory means (910) for processing and storing instructions and data, **characterized** in that it is arranged to inform its capabilities in relation to at least one of the following: time slot configuration, modulation type, bit rate, and capability class, to said system for the examination of fulfilment of point-to-multipoint MBMS (Multimedia Broadcast/Multicast Service) service reception requirements.
- 31. (original) The terminal of claim 30, characterized in that said informing is to be included in a join request for a multicast service.
- 32. (original) The terminal of claim 30, characterized in that it is substantially a GSM (Global System for Mobile communication) or UMTS (Universal Mobile Telecommunications System) terminal.

- 33. (original) A network element (918) operable (920) in a wireless system, comprising processing means (923) and memory means (921) for processing and storing instructions and data, **characterized** in that it is arranged to send a message indicating requirements in relation to at least one of the following: time slot configuration, modulation type, bit rate, and capability class, for point-to-multipoint MBMS (Multimedia Broadcast/Multicast Service) service reception to be delivered to at least one wireless terminal within the service range in order to allow said wireless terminal to determine whether it is capable of receiving the service or not.
- 34. (original) The network element of claim 33, characterized in that said message to be sent is a point-to-multipoint message.
- 35. (original) The network element of claim 33, characterized in that it is arranged to define said requirements for receiving said point-to-multipoint service.
- 36. (original) The network element of claim 33, characterized in that it is arranged to receive said requirements for point-to-multipoint service reception prior to indicating them.
- 37. (original) The network element of claim 33, characterized in that it is arranged to insert said indication of requirements into said message by at least one identifier associated to a certain set of requirements.
- 38. (original) The network element of claim 33, characterized in that it is arranged to insert said indication of requirements into said message explicitly by at least one parameter.
- 39. (original) The network element of claim 33, **characterized** in that said it is arranged to operate in a GSM (Global System for Mobile communication)/GPRS (General Packet Radio Service) or UMTS (Universal Mobile Telecommunications System) system.
- 40. (original) The network element of claim 33, characterized in that it is arranged to transmit said message to be delivered over radio access network.
- 41. (original) The network element of claim 40, characterized in that said radio access network is GERAN (GSM/EDGE Radio Access Network) or UTRAN (UMTS Terrestrial Radio Access Network).

- 42. (original) The network element of claim 33, characterized in that it is substantially the CBC (Cell Broadcast Centre).
- 43. (original) The network element of claim 33, characterized in that said message to be sent is substantially a schedule message.
- 44. (original) The network element of claim 33, characterized in that said message to be sent is a discrete indication message.
- 45. (original) The network element of claim 33, **characterized** in that said point-to-multipoint service is substantially a broadcast or multicast service.
- 46. (original) The network element of claim 33, characterized in that the air interface in said system is substantially in accordance with DVB (Digital Video Broadcasting) or WLAN (Wireless Local Area Network) specifications.
- 47. (original) A network element (918) operable (920) in a wireless system, comprising processing means (923) and memory means (921) for processing and storing instructions and data, **characterized** in that it is arranged to receive a notification from a terminal in relation to at least one of the following: time slot configuration, modulation type, bit rate, and capability class, and deduce on the basis of said notification whether the terminal is capable of receiving a point-to-multipoint MBMS (Multimedia Broadcast/Multicast Service)service or not.
- 48. (original) The network element of claim 47, characterized in that it is arranged to accept or reject the terminal's join request based on said decision.
- 49. (original) The network element of claim 47, characterized in that said point-to-multipoint service is substantially a multicast service.
- 50. (original) The network element of claim 47, characterized in that the air interface in said system is substantially in accordance with DVB (Digital Video Broadcasting) or WLAN (Wireless Local Area Network) specifications.
- 51. (original) A system comprising a network element (918) and at least one wireless terminal (900) operable in said system, characterized in that said network element (918) comprises means (920) for sending a message indicating requirements for point-to-multipoint

MBMS (Multimedia Broadcast/Multicast Service) service reception in relation to at least one of the following: time slot configuration, modulation type, bit rate, and capability class, to be delivered to at least said wireless terminal (900) within the service range and said terminal (900) comprises means (906, 914, 915, 910) for receiving said broadcast message indicating requirements for point-to-multipoint service reception and means (908) for determining on the basis of said requirements whether it is capable of receiving the service or not.

- 52. (original) The system of claim 51, characterized in that said message to be sent is a point-to-multipoint message.
- 53. (original) The system of claim 51, characterized in that said network element (918) further comprises means (923) for defining said requirements for point-to-multipoint service reception.
- 54. (original) The system of claim 51, characterized in that said network element (918) further comprises means (920) for receiving said requirements for point-to-multipoint service reception prior to sending said message indicating said requirements.